







TABLA DE CARGA SEGURA DE TRABAJO ESLINGAS TUBULARES



RHINO SLING

POLYESTER SLING-WIRE ROPE SLING

Tipos de enganche		Carga límite de trabajo (WLL)					
							
Diámetros		Dos Ramales					
Tonelada	Color Forro	Axial	Lazo	Doble o en U	60°	45°	30°
1	Lila	1,0	0,8	2,0	1,7	1,4	1,0
2	Verde	2,0	1,6	4,0	3,4	2,8	2,0
3	Amarillo	3,0	2,4	6,0	5,2	4,2	3,0
4	Gris	4,0	3,2	8,0	6,9	5,6	4,0
5	Rojo	5,0	4,0	10,00	8,6	7,0	5,0
6	Marrón	6,0	4,8	12,0	10,3	8,4	6,0
8	Azul	8,0	6,4	16,0	13,8	11,2	8,0
10	Naranja	10,0	8,0	20,0	17,2	14,0	10,0
11		11,0	8,8	22,0	18,9	15,4	11,0
12		12,0	9,6	24,0	20,6	16,8	12,0
13		13,0	10,4	26,0	22,4	18,2	13,0
14		14,0	11,2	28,0	24,1	19,6	14,0
15		15,0	12,0	30,0	25,8	21,0	15,0
20		20,0	16,0	40,0	34,4	28,0	20,0
25		25,0	20,0	50,0	43,0	35,0	25,0
30		30,0	24,0	60,0	51,6	42,0	30,0
40		40,0	32,0	80,0	68,8	56,0	40,0
50		50,0	40,0	100,0	86,0	70,0	50,0
60		60,0	48,0	120,0	103,2	84,0	60,0
70		70,0	56,0	140,0	120,4	98,0	70,0
80		80,0	64,0	160,0	137,6	112,0	80,0
90		90,0	72,0	180,0	154,8	126,0	90,0
100	100,00	80,0	200,0	172,0	140,0	100,00	

Factor de seguridad 5:1 y 7:1

(*) Los valores están en toneladas métricas

